

# Introduction to Computing

Expressions

# Recap

- Computation
  - How do computers compute - Von Neumann Architecture
- How do computer store data - memory
  - Bits and Bytes
  - There is a unique memory address for each Byte
- What can computer store - numbers
  - Binary number system
  - Operations on binary numbers
- Data, Information

# Recap (contd.)

- Computer Programming
- Computer Programming Languages
  - Machine language - set of instructions
  - High-level programming languages - C, C++, Python
- Steps of Programming
  - Write a program using high-level programming language
  - Compile a program using a compiler to get the machine understandable code
  - Execute the program on machine
  - Anatomy of Programming

# Anatomy of Programming

- Represent the problem formally
- Take a decision
  - Some tasks based on the decision
  - Evaluate outcomes
- Repeat until problem is solved.

# Structure of a C Program

- They are a collection of functions
- Exactly one special function called “**main**” which must be present
- Each function has statements
  - e.g. declaration, assignment, condition check, looping
  - Statements are executed one by one

# The Customary First C Code

↑ The preprocessor

↑ A function definition

↑ *Start of the function*

↑ *A comment*

↑ *A function call*

↑ *A return value*

↑ *End of the function*

```
#include <stdio.h>
```

```
int main (void)
```

```
{
```

```
    /* my first program in C */
```

```
    printf ("Hello, World! \n");
```

```
    return 0;
```

```
}
```

# Things One Might Use in C Programming

- **Variables**
- **Constants**
- **Expressions**
  - Arithmetic, Logical, Assignment
- **Statements**
  - Declaration, Assignment,
  - Control Structures - conditional branching, looping
- **Arrays**
- **Pointers**
- **Functions**
- **Structures**

# Variables and Constants

- A variables has a **name**, a **memory address** and a **datatype**
- Name
  - A sequence of letter and digits with first symbol being a letter or '\_'
- Types of Variables
  - int, float, double, char, struct, pointer, array, void, etc
- Variables stored in memory
  - Therefore, each variable has an unique address
  - Each type has a predefined size - *typically they have standard values, but sometimes it may depend on the software/system you are using*
- Constants are basically read-only variables
  - Values, once assigned, cannot be changed



# Expressions

- Variables and constants linked with operators
- Every expression evaluates to a value

- Arithmetic expressions
  - Uses arithmetic operators
  - Can evaluate to any value
- Logical expressions
  - Uses relational and logical operators
  - Evaluates to 0 (false) or 1 (true) only
- Assignment expressions
  - Uses arithmetic operators
  - Evaluates to value depending upon assignment

# Arithmetic Operators

- Binary operators

- Addition +
- Subtraction −
- Multiplication \*
- Division /
- Modulus %

- Unary operators

- Plus +
- Minus −

- All operator except % can be used with operands of any data types

- int, float, double, char

- % can be used only with integer operands

# Operator Precedence

## In decreasing order of priority

- Parenthesis ()
- Unary minus –
- Multiplication \*, Division / and Modulus %
- Addition + and Subtraction –

- For same priority evaluation is done from **left to right** as they appear
- Parenthesis may be used to change the precedence of operator evaluation

# Arithmetic Expressions (contd.)

## Examples

- $1 + 2 * 3$ 
  - $1 + (2 * 3) \Rightarrow 7$
- $8 / 2 + 2 * 3$ 
  - $(8 / 2) + (2 * 3) \Rightarrow 10$
- $a - b + c + d$ 
  - $((a - b) + c) + d$
- $a * -b + d \% e - f$ 
  - $a * (-b) + (d \% e) - f$

## Let's test your understanding ...

- $a + b + c * d * e \Rightarrow ?$
- $10 / 5 \Rightarrow ?$
- `int a = 10, b = 20, c = 30, d ;`  
`float f;`
  - $d = b/a; d \Rightarrow ?$
  - $d = a/b; d \Rightarrow ?$
  - $d = c/b; d \Rightarrow ?$
  - $f = c/b; f \Rightarrow ?$

# Assignment Operator

- l-value = r-value
- l-value must be a variable where you can assign data
- r-value can be any valid for of expression
- The types of both side should usually be the same
- In the other case, r-value gets internally converted to the type of l-value
  - This can cause problems
  - e.g. `int a; a = 2 * 3.3; ⇒ a = 6` and not 6.6

# Assignment Expression

- Uses the assignment operator =
- General syntax:
  - `variable_name = expression`
  - l-value = r-value
- The value of the assignment expression is the value assigned to the l-value

## ● Examples:

- $a = 7 \Rightarrow 7$
- $b = 2 * 7 - 11 \Rightarrow 3$
- $c = x + y * 3 - z \Rightarrow$  whatever value the arithmetic expression  $x + y * 3 - z$  evaluates to; depends on the value of  $x, y, z$
- $a = a + 5 \Rightarrow 12$

## Assignment Expression (contd.)

- Several variables can be assigned to the same value using multiple assignment operators
  - `a = b = c = 10`
  - `x = y = 'a'`
  - ... and so on
- Multiple assignment operators are **right-to-left** associative
- Each of the assignment expressions are evaluated to a value and that value propagates to the next one

# Assignment Operator Variations

- There are shortcuts for simple assignments

- `+=`, `-=`, `*=`, `/=`, `%=`

- $a += b \Rightarrow a = a + b$

- $a *= 2 \Rightarrow a = a * 2$

- ... and so on.

- Let's test your understanding

...

- `int a, b, c;`

- Case 1

- `a = b = c = 5`

- `a = ? b = ? c = ?`

- Case 2

- `a=3; b= 5;`

- `a += b+= 1;`

- `a = ? b = ?`



## Two More Variations

- Two unary variations which increments or decrement the value of the operand by 1
  - Pre-increment operator, Post-increment operator ++
  - Pre-decrement operator, Post-decrement operator --
    - $a++ \Rightarrow a = a + 1$
    - $++a \Rightarrow a = a + 1$
- Both pre and post operators increment/decrement the value, but there is an important difference in the evaluated value of that expression
    - $a = 3;$
    - $a++ \Rightarrow 3$
    - $++a \Rightarrow 4$

# Logical Expressions

- Uses relational and logical operators
- This generally specifies a condition which can be either true or false

- Relational operators

- $>$        $>=$

- $<$        $<=$

- $==$        $!=$

... compares two quantities

## Logical Expressions (contd.)

- Examples

- $x \leq y$
- $x == y$
- $1 == 2$
- $x == y == 1$

- $(x + y < 6) \Rightarrow x + y < 6$

- Evaluates to either 0 or 1

- $0 \Rightarrow$  **false**
- $1 \Rightarrow$  **true** ; *also non-zero values*

- Arithmetic expressions are evaluated first when on either side of a relational operator

# Logical Operators

## LOGICAL AND

**&&**

- $0 \ \&\& \ 0 \Rightarrow 0$
- $0 \ \&\& \ \text{non-zero} \Rightarrow 0$
- $\text{non-zero} \ \&\& \ 0 \Rightarrow 0$
- $\text{non-zero} \ \&\& \ \text{non-zero} \Rightarrow 1$

## LOGICAL OR

**||**

- $0 \ || \ 0 \Rightarrow 0$
- $0 \ || \ \text{non-zero} \Rightarrow 1$
- $\text{non-zero} \ || \ 0 \Rightarrow 1$
- $\text{non-zero} \ || \ \text{non-zero} \Rightarrow 1$

## LOGICAL NOT

**!**

- $!0 \Rightarrow 1$
- $!\text{non-zero} \Rightarrow 0$
- aka. unary  
negation operator

# Logical Expressions (contd.)

## Examples

`x = 1, y = 3, grades = 'B'`

- `(x + y < 6) || (y >= 9) ⇒ 1`
- `(x == y) && (y != 5) ⇒ 0`
- `!(grades == 'A') ⇒ 1`

## Let's test your understanding

- `(!10) || (10 + 20 != 200) ⇒ ?`
- `(!10) && (10 + 20 != 200) ⇒ ?`
- `(4 > 3) && (100 != 200) ⇒ ?`
  
- `(x + y > 6) || (y >= 9) ⇒ ?`
- `(x = y) && (y == 1) ⇒ ?`
- `grades == 'B' ⇒ ?`
- `x = 3 && (y = 4) ⇒ ?`

# Bitwise Operators

- Operators that permits operation on individual bits
- Useful for low level programming such as controlling hardware

*... we will discuss this operators in more details later on (if time permits).*

- Bitwise AND &
- Bitwise OR |
- 1s complement ~
- Bitwise XOR ^
- Left shift <<
- Right shift >>

## A Special Operator: AddressOf (&)

- Remember that each variable is stored at a location with an unique address
- Putting & before a variable name gives the address of the variable (where it is stored, not the value)
- Can be put before any variable (with no blank in between)
  - `int a = 8;`
  - `printf ("value of a = %d, address of a=%d", a, &a);`
  - `printf ("value of a = %d, address of a=%p", a, &a);`

## Another Special Operator: **sizeof** ()

- This is a much used operator in C
- It is an unary operator
- It is used to compute the size of its operand in compile time
- It can be used on any data type
  - `sizeof (int)`, `sizeof (char)`,  
*int a; sizeof (a)*, etc.
- It can be used with an expression as well – then it returns the size of the final value
  - `int a=2; double b=10.3;`
  - `sizeof(a+b) ⇒ sizeof(double)`



# Typecasting

- Remember the **problem** with division
  - `int a = 10, b = 20, c = 30, d ; float f;`
  - `f = c/b; f ⇒ ?`
- The solution is to do the following
  - Convert at least one of the operand to floating point
  - `f = c; f ⇒ 30.0`
  - `f /= b; or f = f/b; f ⇒ 1.50`
- The shorthand of doing this is called typecasting
  - `f = ((float)c)/b; f ⇒ 1.50`
  - The type of `c` has not changed but the evaluated value of `(float)c` is now a float type

## Typecasting (contd.)

- Not everything can be typecast to everything
  - Casting a float to an integer will lose information since int cannot store the fractional part
  - Similarly **int** should not be typecast to **char**
- General rule
  - Make sure the final type can store any value of the initial type

# Statements in a C Program

- Parts of C program that tell the computer what to do
- Types of statements
  - Declaration statements – Declares variables etc.
  - Assignment statement – Assignment expression, followed by a ;
  - Control statements – For branching and looping
    - Branching - if-else, switch
    - Looping - for, while, do while
  - Input/Output – Read/print, like printf/scanf

## Statements (contd.)

- Compound statements
  - A sequence of statements enclosed within { and }
  - Each statement can be an assignment statement, control statement, input/output statement, or another compound statement
  - We will also call it block of statements sometimes informally